



elemental



P61

The weather-tight choice for locations where a wet-location fixture is put to the test.



Dew. Rain. Sleet. Snow. With P61, it's no problem.

The P61 has always been UL wet-listed, suitable for locations where moisture poses a constant threat to the performance and safety of light fixtures. And now the engineers at Prudential Ltg. have made our P61 even more weather-tight, with an improved one-piece gasketed doorframe. It seals the P61 tight to keep moisture from gaining a foothold with the body of the fixture.



Our P61 is now an even better choice for locations such as parking garages that are exposed to wet weather, thanks to a new one-piece gasketed door design.

Along with high impact acrylic shielding and optional emergency batteries, low-temp ballasts, and tamper resistant fasteners, the P61 is ideal for high-exposure areas such as parking structures. Our P61 has other improvements. There are new brackets and spacers for greater stability and ease of installation. And it now offers improved direct symmetric and asymmetric performance. But one thing hasn't changed:

Its classic 6" square profile still blends perfectly with any architectural setting.



The classic simplicity of its 6" square profile makes the P61 the perfect fixture to complement a wide range of architectural settings.

series	lamp rows	nominal length	shielding	color/finish	distribution	circuiting	voltage	mounting	options
P61									
	1T8	02'	HCA*	TMW textured matte white	D1 direct	SC single circuit	120	SUR surface mount to ceiling	EML-DL
	2T8	03'			D4W* asymmetric toward wall	DC* dual circuit (in-line)	277		EMH-DL
	1T5	04'	WA	YGW* gloss white	D4R* asymmetric toward room		347*	WB wall bracket (3")	DM
	2T5	R_*		YPE pewter			MVB** multi-volt ballast		RSE
	1T5HO			Y_ premium color				WS wall spacer (3/4")	10THD
	2T5HO			CC custom color					B_
									LT
									FH
									TRS
		*row length	*standard	*standard	*1lamp only	*2 lamp only	*T8 & T5HO only **120-277		

applications Exterior wall mounts, parking structures, commercial roll-up door applications.

features An aluminum 6" x 6" wet location luminaire. It features a one-piece gasketed door frame. Available with one or two T5/HO or T8 lamps in cross-section. The fixture also offers a choice of symmetric or asymmetric light patterns.

construction The housing, available in 2-, 3- or, 4-foot standard lengths, is made of 18-gauge aluminum, and can be through-wired for continuous row applications.

finish The standard housing is gloss white (YGW) using polyester powder paint.

electrical T8 fixtures have instant-start electronic ballasts with less than

20% THD. T5 and T5HO fixtures have programmed-start electronic ballasts with less than 10% THD. Fixtures are I.B.E.W. manufactured and U.L. labeled "Suitable for wet locations" and "Suitable for Mounting within 4-feet of the ground". Maximum ballast size available: 1-5/8" width x 1-1/4" height.

mounting Fixture is to be surface ceiling- or wall-mounted.

options **EML-DL:** damp listed emergency ballast (600-700 lumens); **EMH-DL:** damp listed emergency ballast (1100-1400 lumens); **DM:** dimming (consult factory); **RSE:** rapid-start electronic; **10THD:** ballast with < 10% total harmonic distortion; **B_:** specific ballast, specify manufacturer and catalog number (consult factory); **LT:** low temperature ballast; **FH:** fixture fusing (slow blow); **TRS:** tamper resistant hardware.



Waste not, want not. As part of our efforts to ensure we practice sustainability in our business, we've printed this brochure on recycled paper.



Light creates Life.
Create with Prudential Ltg.
213.746.0360
prulite.com