



Bolt Pentagon | Pendant, Surface & Wall




PRUDENTIAL LTG.

PRULITE.COM 213.746.0360



Type:

Job:



Working all the angles.

Forgettable, this new shape is not. Bolt is offered in Triangle, Square, Pentagon and Hexagon configurations commanding attention wherever it goes. It inspires, giving architects and lighting designers new fodder for thought.

BPEN-LED35-LO
5094 Delivered Lumens
41 Watts
125 lm/w

UPTO **125** LPW

	LO	MO	SO	HO
lm	5000	6800	8000	9800
w	41	56	70	87

(CLICK HERE)

Declare.



Made in the USA

Lumen output may vary +/- 5%
3500K used for lm/ft estimates above
4000K +2% llf, 3000K -2%, 2700K -4%
-10% LLF for 90 CRI (4K, 3500K and 3K)


See LED Details PDF for more info

SERIES	NOMINAL LENGTH	LED COLOR	OUTPUT	SHIELDING	COLOR/ FINISH	VOLTAGE	MOUNTING	CEILING SYSTEMS	DRIVERS	OPTIONS & SENSORS
BPEN	22			SAL						
Bolt Pentagon	22 2 x 2' x 2' x 2 x 2' (41" Diameter)	LED27 2700K (90CRI) LED3 3000K LED35 3500K LED4 4000K LED3-90 90CRI LED35-90 90CRI LED4-90 90CRI	LO Low MO Medium SO Standard HO High PROG Pro-gramma-ble Light Output (Specify desired lm/ft or w/ft)	SAL Satin Acrylic Lens	TMW Textured Matte White YGW Gloss White (Standard) Y__ Premium Color CC Custom Color NOTE: All canopies are painted the same color as the fixture. Consult factory to specify	UNV (120-277) 347 (Emergency battery requires a Step Down transformer)	CA48", 96" or 144" Aircraft Cable (Adjustable) 5RPM48", 96" or 144" Round Cast Aluminum Canopy (24" min from fixture to ceiling) 5SPM48", 96" or 144" Square Cast Aluminum Canopy (24" min from fixture to ceiling) SUR Surface or Wall Mount	X1 T-Bar 1 3/4" or 1 1/2" Exposed (Standard) X3 Hard Ceiling X6 Slot Grid or Interlude	ND Non-Dimming DM01 0-10v, 1% Dimming (Standard) LDE1 Lutron Hi-lume 1% EcoSystem LED (Soft fade on, fade-to-black dimming) ECO 1% 0-10v, EldoLED (Logarithmic dimming std) ECDA 1% DALI, EldoLED (Logarithmic dimming std) SOLO 0.1% 0-10v, EldoLED (Dim-to-dark, Logarithmic dimming std) SODA 0.1% DALI, EldoLED (Dim-to-dark, Logarithmic dimming std)	EMHE CA T20 Emergency Battery (1250 delivered lumens; CA Title 20 compliant; remote only) PRUBIN Meticulous Binning and Labeling every LED Board within a 2-Step MacAdams Ellipse SENSORS: 205-ON/OFF-WattStopper PIR Occupancy 205-STEP: Dim to 50% 205-DM: Dim to 1% ENL Enlighted 2-Wire DLH & Environmental



PHOTOMETRICS

Low Output:
BPEN-LED35-LO
 5094 Delivered Lumens
 41 Watts
 125 lm/w
 3500 CCT
 Test
 #103624486LAX-007



Zonal Lumen Summary:
 0-90 (Down) = 89%
 90-180 (Up) = 11%

Vertical Angle	0°	25°	45°	65°	90°
0°	1384	1384	1384	1384	1384
5°	1373	1374	1377	1381	1380
15°	1323	1321	1319	1322	1323
25°	1212	1210	1203	1210	1222
35°	1068	1056	1058	1072	1068
45°	916	904	906	920	920
55°	766	754	758	774	774
65°	605	595	599	617	617
75°	437	427	432	451	449
85°	276	265	270	288	283
90°	148	134	136	154	147
95°	154	144	144	158	148
105°	115	111	118	137	135
115°	100	97	98	105	103
125°	82	79	74	81	75
135°	66	65	62	64	60
145°	64	56	54	59	51
155°	44	40	40	40	37
165°	26	24	25	24	23
175°	11	11	10	11	10

LUMEN MAINTENANCE

Designed to last with cool running mid-power LEDs projected to maintain 90% (L90) of their initial output for 100,000 hours (at HO), and L70 exceeding 150,000 hours.

LED SYSTEM LED modules and drivers are field replaceable.

PROG (OPTIONAL) Programmable light output. Specify desired lumens or watts per fixture.

BINNING Standard binning (all Prudential LED boards) includes testing at the chip level and board integration to provide consistent color temperature within a 3-step MacAdams ellipse, with +/- 5% lumen output range and +/- .004 Duv.

PRUBIN* (OPTIONAL) Prudential Ltg's exclusive 'job binning' method that ensures color temperature consistency across all luminaires on a project. Meticulously testing and labeling **EVERY LED BOARD** to +/- 25 lumens, +/- 50k CCT and +/- .004 Duv — while also separating positive from negative — allows us to match color, hue and intensity throughout a project and provides a consistent color temperature within a 2-step MacAdams ellipse.

LABELS CSA and ETL damp labeled and I.B.E.W. manufactured.

ELECTRICAL Must specify LED dimming controls. LED fixtures have constant current driver(s) with less than 20% THD when loaded to a minimum of 60%. Drivers sink a maximum of 6mA per driver. DM01 LED drivers are 0-10V dimmable and are compatible with most 0-10V wall slide dimmers and direct 0-10V analog signal dimmers. Max driver size 1¼" w x 1" h.

CONSTRUCTION

Housing Extruded aluminum, 25% PC recycled, 100% recyclable

Lens Extruded acrylic, 100% recyclable

Weight 20 lbs

MOUNTING Fixture is to be suspended with aircraft cables or surface mounted.

WARRANTY Single-source, 5 year limited warranty covers standard components and construction.



YSW – Seashell White (Matte)	YCH – Champagne (Metallic)
YSL – Silver (Metallic)	YPE – Pewter (Matte)
YRG – Rain Grey (Gloss)	YSTM – Storm Grey (Matte)
YBK – Black (Matte)	YBB – Black (Semi Gloss)
YSKM – Sky (Matte)	YMB – Military Blue (Matte)
YIB – Interstate Blue (Matte)	YSAM – Sapphire (Matte)
YFGM – Forest Green (Matte)	YBR – Bronze (Matte)
YBY – Boysenberry (Matte)	YSRM – Sunset Red (Matte)
YOR – Orange (Matte)	YDAM – Daffodil (Matte)



Choose from one of our Premium Colors with no set-up fee.

For paint chip samples, please email: info@prulite.com

SENSOR BOX



205
WattStopper PIR Occupancy




ENL
Enlighted 2-Wire PIR Daylight,
Motion & Environmental Sensor

Consult factory for other sensors.


NOTE: Sensor plate will match fixture color

SENSOR MOUNTING LOCATION




Sensor box is always centered in one lens

MOUNTING




CA48", 96" & 144": 5" Canopies


MOUNTING DIMENSIONS



5RPM48", 96" or 144": Round Cast Aluminum Canopy



5SPM48", 96" or 144": Square Cast Aluminum Canopy



NOTE: Canopies cannot mount directly to t-bar grids

