Prudential Lighting

Light measurement results

Print date 8/13/2026

Laboratory and Equipment

Test lab	Viso LabSpion - serial: 2435469709 sensor serial: 0895736217 - T
Spectrometer Manufacturer and Model	LabSpion – Type C, horizontal
Measurement date	7/24/2026

Measurement Conditions

Tested c-planes	72 planes – 5.00°
Tested gamma resolution	1.00°
Input Power	15.63 W

Tested Light Source


Luminaire	BPRO2-LIN-FLSH-LED35-LO-04-MGZ-NU-SC-DM01
Basic Luminous Shape	NONE
Item No.	
Manufacturer	Prudential Lighting
Description	

Main Light Measurement Results

Output – Total Lumen (Up% / Down%)	1900 lm – 1.604% / 98.4%
Efficiency	121.5 lm/W
Peak Intensity	1464 cd
Correlated Color Temperature, CCT	3431 K
Color Rendering Index	CRI 84.3

Polar light distribution diagram


Unit: 0-100% of peak intensity



Zonal Lumen Summary:

VA/HA	0°	22.5°	45°	67.5°	90°
0°	1449 cd	1449 cd	1449 cd	1449 cd	1449 cd
5°	1436 cd	1372 cd	1291 cd	1225 cd	1248 cd
15°	1339 cd	1090 cd	864.5 cd	762.4 cd	752.8 cd
25°	1154 cd	825.5 cd	624.2 cd	552.2 cd	542 cd
35°	899.9 cd	617.9 cd	461.5 cd	408.6 cd	402.8 cd
45°	629.8 cd	443.9 cd	333.1 cd	298.6 cd	294.9 cd
55°	388.2 cd	297.4 cd	229.7 cd	207.7 cd	208.1 cd
65°	209.8 cd	177.2 cd	142.9 cd	130.3 cd	133.4 cd
75°	94.1 cd	86.75 cd	70.83 cd	66.74 cd	66.48 cd
85°	22.38 cd	21.34 cd	18.04 cd	15.77 cd	16.62 cd
90°	1.469 cd	3.845 cd	0.9872 cd	1.252 cd	1.253 cd

Spectral power distribution




Prudential Lighting

Light measurement results

Print date 8/13/2026

Luminous Intensity diagram

Unit: 0-100% of peak intensity



Main Values

Output (total Lumen)	1900 lm
Lumen Up% / Down%	1.604% / 98.4%
Peak Intensity	1464 cd
Beam Angle (50%-FWHM)	49.1°

EU Ecodesign parameters


Directionality (DLS or NDLS)	DLS
Ecodesign Useful Luminous Flux	1231 lm
Ecodesign Energy Class	F

Intensity Ratio

In 120° cone	84.72%
In 90° cone	64.8%

Linear distribution diagram

Intensity [cd]




Prudential Lighting

Light measurement results

Print date 8/13/2026


Iso-intensity Diagram (Iso-candela)



90 %	1316.4 cd
80 %	1170.1 cd
70 %	1023.9 cd
60 %	877.6 cd
50 %	731.3 cd
40 %	585.1 cd
30 %	438.8 cd
20 %	292.5 cd
10 %	146.3 cd

Peak intensity: 1462.7 cd
Number of c-planes: 72

Iso-illuminance Diagram (Iso-lux)



50.0 %	81.2 lx
30.0 %	48.7 lx
10.0 %	16.2 lx
5.0 %	8.12 lx
3.0 %	4.87 lx

Peak illuminance: 162 lx
Mounting height: 3 m
Number of c-planes: 72

Prudential Lighting


Light measurement results

Print date 8/13/2026


Color details

Correlated Color Temperature, Target	CCT = 3431 K	MacAdam Steps	SDCM = NaN
Correlated Color Temperature, Measured	CCT = 3431 K	Color deviation from BBL	Duv = 0.0016
Color Rendering Index	CRI 84.3	Color coordinates CIE 1931	(x;y) = (0.4112;0.3972)
Color Rendering Index, R9 (red)	R9 = 11.0	Color coordinate CIEs 1960	(u;v) = (0.2369;0.3432)
Color Rendering TM30-18	Rf 85.5	Color coordinate CIEs 1976	(u';v') = (0.2369;0.5148)
	Rg 95.8	Color Quality Scale	CQS = 84.1


CIE 1931 Chromaticity diagram




Spectral power distribution



CIE 1931 Chromaticity - zoomed




Color Rendering Index per reference color (CIE 1995)




CRI R values, only R1-R8 are used to calculate final CRI value

R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15
82.8	90.8	97.0	83.6	82.7	88.3	85.4	63.3	11.0	78.7	83.8	65.7	84.9	98.7	74.7

CIE 1931 Chromaticity - SDCM



TM30-18 Rf-values per hue bin



TM30-18 Rf-values per hue bin

C1	C2	C3	C4	C5	C6	C7	C8	C9	C10	C11	C12	C13	C14	C15	C16
80.7	83.4	81.2	90.2	92.0	94.8	90.8	93.9	88.7	81.1	79.2	86.6	89.4	81.1	80.1	78.5


Prudential Lighting

Light measurement results

Print date 8/13/2026

Color details - ANSI/IES TM-30-18 Color Rendition Report


Color Vector Graphic




Color Distortion Graphic



Gamut Index vs. Fidelity Index




Color Rendition by Color Evaluation Sample (CES)




Color evaluation sample CES01 through CES99

Local Color Fidelity (per hue bin)



Local Chroma Shift (per hue bin)



CIE x	0.4112
CIE y	0.4112
CIE u'	0.2369
CIE v'	0.5148


CIE	**13.3-1995**
Ra	84.3
R9	11.0

Prudential Lighting

Light measurement results


Print date 8/13/2026

Beam details



Luminaire budgetary diagram

LAMPS (number of lamps)



Intensity details

Beam intensities from 1 – 20 m

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	m
3.3	6.6	9.8	13.1	16.4	19.7	23	26.2	29.5	32.8	36.1	39.4	42.7	45.9	49.2	52.5	55.8	59.1	62.3	65.6	ft
1449	362	161	91	58	40	30	23	18	14	12	10	9	7	6	6	5	4	4	4	lux
134.6	33.7	15	8.4	5.4	3.7	2.7	2.1	1.7	1.3	1.1	0.9	0.8	0.7	0.6	0.5	0.5	0.4	0.4	0.3	fc

Intensities in 0° c-plane

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°	γ
1449	1436	1399	1339	1255	1154	1033	900	766	630	501	388	290	210	145	94	53	22	1	3	cd
100%	99%	97%	92%	87%	80%	71%	62%	53%	43%	35%	27%	20%	14%	10%	6%	4%	2%	0%	0%	of 0°val

Intensities in 90° c-plane

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°	γ
1449	1248	949	753	632	542	466	403	345	295	249	208	172	133	99	66	40	17	1	0	cd
100%	86%	65%	52%	44%	37%	32%	28%	24%	20%	17%	14%	12%	9%	7%	5%	3%	1%	0%	0%	of 0°val

Intensities in 180° c-plane

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°	γ
1449	1440	1406	1349	1270	1168	1054	925	789	652	525	405	304	219	152	101	57	24	2	2	cd
100%	99%	97%	93%	88%	81%	73%	64%	54%	45%	36%	28%	21%	15%	10%	7%	4%	2%	0%	0%	of 0°val

Intensities in 270° c-plane

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°	γ
1449	1249	954	759	636	540	461	395	338	286	239	198	159	124	90	60	34	13	1	1	cd
100%	86%	66%	52%	44%	37%	32%	27%	23%	20%	16%	14%	11%	9%	6%	4%	2%	1%	0%	0%	of 0°val

Prudential Lighting

Light measurement results

Print date 8/13/2026

UGR Table

Corrected, comprehensive UGR table according to 117-1995, S/H ratio=0.25

Reflectances											
ρ Ceiling	70	70	50	50	30	70	70	50	50	30
ρ Walls	50	30	50	30	30	50	30	50	30	30
ρ Floor	20	20	20	20	20	20	20	20	20	20
Room size		**Viewed Crosswise**					**Viewed Endwise**				
H = mouting height above eye level		(Viewing direction orthogonal to lamp length axis)					(Viewing direction parallel to lamp length axis)				
X	**Y**										
	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
Variations with the observer position for the luminaire spacings, S:											
n/a		n/a					n/a				
n/a		n/a					n/a				
n/a		n/a					n/a				

UGR data could not be calculated due to missing light source dimensions. Go to Edit -> Photometric -> Dimensions and set the source dimensions.

Coefficients of utilization

Ceiling reflectance	80				70				50			30			10			0
Wall reflectance	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
Floor reflectance	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20
RCR	(Room Cavity Ratio)				Room values are expressed as percentage of Lumen delivered to the task surface													
0	118.7	118.7	118.7	118.7	115.7	115.7	115.7	115.7	110.2	110.2	110.2	105.2	105.2	105.2	100.6	100.6	100.6	98.4
1	109.9	105.8	102.1	98.7	107.1	103.4	100.0	97.0	98.9	96.2	93.7	94.8	92.6	90.5	91.0	89.2	87.6	85.5
2	101.3	94.1	88.2	83.2	98.7	92.1	86.7	82.1	88.4	83.9	79.9	85.0	81.2	77.9	81.8	78.8	76.0	73.9
3	93.5	84.2	77.1	71.3	91.1	82.6	76.0	70.6	79.5	73.8	69.2	76.6	71.8	67.8	74.0	69.9	66.5	64.4
4	86.6	75.9	68.1	62.2	84.3	74.6	67.3	61.7	71.9	65.7	60.7	69.5	64.1	59.7	67.3	62.6	58.8	56.8
5	80.4	68.9	60.9	54.9	78.4	67.7	60.2	54.6	65.5	58.9	53.8	63.5	57.7	53.2	61.6	56.5	52.5	50.5
6	75.0	62.9	54.9	49.1	73.1	61.9	54.3	48.8	60.1	53.3	48.3	58.3	52.3	47.8	56.7	51.4	47.3	45.3
7	70.1	57.8	49.8	44.3	68.4	56.9	49.4	44.1	55.3	48.6	43.7	53.8	47.8	43.3	52.4	47.0	42.9	41.0
8	65.7	53.4	45.6	40.3	64.2	52.6	45.2	40.1	51.2	44.6	39.8	49.9	43.9	39.5	48.7	43.3	39.2	37.4
9	61.8	49.5	42.0	36.9	60.4	48.9	41.7	36.8	47.7	41.1	36.5	46.5	40.6	36.3	45.5	40.0	36.0	34.3
10	58.3	46.1	38.9	34.0	57.0	45.6	38.6	33.9	44.5	38.1	33.7	43.5	37.7	33.5	42.6	37.2	33.3	31.7

Prudential Lighting

Light measurement results

Print date 8/13/2026

Power details

Input power	
Frequency of input power	60.0 Hz
Power feed to light source	15.63 W
RMS Input voltage feed V,RMS	120 V
RMS Input current feed I,RMS	0.13 A
Volt-Amp or apparent power = V,RMS*I,RMS	15.8 VA
Displacement factor of AC power feed	0.99
Power factor of AC current feed	0.99
Total harmonic distortion of the current	6.479%
Total harmonic distortion of the voltage	0.054%

Input power curve




Efficiency

Radiated power efficiency	36.2
Lumen efficiency	121.5 lm/W

Stabilization details

Warmup Conditions		Color Temperature Change	
Stable period	15 min	CCT start	3432 K
Stable change max	1%	CCT shift	-1 K
Minimum time	15 min	CCT end	3431 K
Warmup Result		**Output Change**	
Total warmup time	Not completed	Output start	1903 lm
Warmup variation	-0.6803%	Output change	-3.4118 lm
		Output end	1900 lm

Stabilization Curve



Prudential Lighting

Flicker TLA details

Flicker Meter Type	Viso Systems LabFlicker
Frequency of input power	60.0 Hz
Flicker/TLA sample rate	NaN samples/s

Measurement time

PstLM	180 sec.
All other indices	1,5 sec,

Flicker indices according to Illuminating Engineering Society (IES)

Flicker frequency	NaN Hz
Percent Flicker	NaN %
Flicker index	NaN

TLA indices (re IEC TR 61547-1, IEC 61000-3-3 and IEC 61000-4-15)

PstLM value (F < 80 Hz)	NaN
SVM value (80 < F < 2000 Hz)	NaN


Flicker indices according to California Energy Commission (CEC) 2016b

JA8/10 40 Hz	NaN %
JA8/10 90 Hz	NaN %
JA8/10 200 Hz	NaN %
JA8/10 400 Hz	NaN %
JA8/10 1000 Hz	NaN %


Flicker indices according to Lighting Research Center (2015)

Perception metric, Assist Mp	NaN

Flicker frame (frame of one flicker period in time domain)



Flicker FFT (flicker curve in frequency domain)



IEEE 1789 Frequency/modulation plot

