



Stream™ Dot | Recessed 4" Square 'Architectural Accent'



PRUDENTIAL LTG.

PRULITE.COM 213.746.0360




Type:

Job:

Dot 'accent' lights punctuate architectural interiors.

Our veiled ambient Stream series of recessed and pendant fixtures now include 4" round and square 'architectural accent' lights to complete a recessed line of light. Soft indirect hidden LEDs reduces glare and offer a wide, even distribution of light. Stream Dots have the same form factor as downlights, but look and perform uniquely Stream-like.



	SDP-6-LED35-SO-NU-UNV-NU	
	791	Delivered Lumens
	10	Watts
	79	lm/w
	3500	CCT

UPTO

79

LPW

LO

MO

SO

HO

lm

400

600

790

1050

w

5.2

7.7

10.1

14

CLICK HERE

Declare.

TechZone6



Made in the USA

Lumen output may vary +/- 5%
3500K used for lm/ft estimates above
4000K +2% If, 3000K -2%, 2700K -4%

SERIES	LED COLOR	OUTPUT	TRIM COLOR	CIRCUIT-ING	VOLTAGE	CEILING SYSTEMS	DRIVERS	OPTIONS
SDOT				SC				
Square Dot	LED27 2700K, 90 CRI LED3 3000K, 90 CRI LED35 3500K, 90 CRI LED4 4000K, 90 CRI	LO Low (Matches 4" recessed SO) MO Medium SO Standard HO High PROG Program- mable Light Output (Specify desired lumen or watts)	TMW Textured Matte White (Standard) YGW Gloss White YSW Seashell White (Premium color) Y_ Premium Color CC Custom Color	SC Single Circuit	UNV (120-277) 347 Requires — • Rough-in box • Remote box for TechZone & X3R (See page 5, Consult factory for Eldo, Lutron)	X1† T-Bar 1 5/16" or 5/8" X1Z Fits TechZone6 X2Z TechZone6 for Dimensional T-Bar or Slot Grid X3 Flanged Hard Ceiling (Remodel) X3R† Flanged Hard Ceiling (New construction) X7† Mud-in Hard Ceiling (Flangeless) † Rough-in Box required	ND Non-Dimming DM01 0-10v, 1% Dimming (Osram Standard for 0-10V) LDE1 Lutron Hi-lume 1% EcoSystem LED (Soft fade on, fade-to-black dimming, SO and HO only) ECO 1% 0-10v, EldoLED (Logarithmic dimming std) ECDA 1% DALI, EldoLED (Logarithmic dimming std) SOLO 0.1% 0-10v, EldoLED (Dim-to-dark, Logarithmic dimming std) SODA 0.1% DALI, EldoLED (Dim-to-dark, Logarithmic dimming std)	EML Emergency Battery (EML not available in certain configurations. See page 5) NOTE: RTK kit required ADC Acrylic Dust Cover (Ships installed) CP Chicago Plenum (NA with X1Z, X2Z & X3R)



Prudential Ltg. reserves the right to change design specifications or materials without notice. Please visit prulite.com for most current data.
© 2014 All rights reserved – All products manufactured at: Prudential Ltg. 1774 E. 21st Street, Los Angeles, CA 90058

Recessed

1

12-12-2023



Stream™ Dot | Recessed 4" Square 'Architectural Accent'



PRUDENTIAL LTG.

PRULITE.COM 213.746.0360

DIRECT

Standard Output:


SDP-6-LED35-SO-NU-UNV-NU

791 Delivered Lumens

10 Watts

79 lm/w

3500 CCT




Zonal Lumen Summary:

0-90 (Down) = 100%

90-180 (Up) = 0%

Vertical Angle	0°	25°	45°	65°	90°
0°	244	244	244	244	244
10°	239	240	240	240	239
20°	230	230	230	229	230
30°	214	214	213	214	214
40°	195	193	193	193	194
50°	169	167	167	167	168
60°	136	135	136	134	135
70°	93	93	96	93	93
80°	5	6	6	5	5
90°	0	0	0	0	0

STREAM SERIES "VEILED AMBIENT" ILLUMINATION



Stream's soft, even hidden light source creates a "skylight" effect.

LUMEN MAINTENANCE

Designed to last with cool running mid-power LEDs projected to maintain 90% (L90) of their initial output for 100,000 hours (at HO), and L70 exceeding 150,000 hours.

LED SYSTEM

LED modules and drivers are field replaceable.

PROG

(OPTIONAL)

Specify desired lumens or watts per fixture. Round Dot min: 5.3 watts, max: 18.4 watts. Square Dot min: 4.7 watts, max: 16.8 watts.

BINNING

Standard binning (all Prudential LED boards) includes testing at the chip level and board integration to provide consistent color temperature within a 3-step MacAdams ellipse, with +/- 5% lumen output range and +/- .004 Duv.

LABELS

IC Rated. CSA and ETL damp labeled and I.B.E.W. manufactured.

ELECTRICAL

Must specify LED dimming controls. LED fixtures have constant current driver(s) with less than 20% THD when loaded to a minimum of 60%. Drivers sink a maximum of 6mA per driver. DM01 LED drivers are 0-10V dimmable and are compatible with most 0-10V wall slide dimmers and direct 0-10V analog signal dimmers.

CONSTRUCTION

Housing

20-gauge steel galvanized housing, >20% PC recycled, 100% recyclable, PAF, Painted After Fabrication & cast aluminum trim.

WARRANTY

Single-source, 5 year limited warranty covers standard components and construction



Prudential Ltg. reserves the right to change design specifications or materials without notice. Please visit prulite.com for most current data.
© 2014 All rights reserved - All products manufactured at: Prudential Ltg. 1774 E. 21st Street, Los Angeles, CA 90058

Recessed

2

12-12-2023



Stream™ Dot | Recessed 4" Square 'Architectural Accent'



PRUDENTIAL LTG.

PRULITE.COM 213.746.0360

YSW – Seashell White (Matte)	YCH – Champagne (Metallic)
YSL – Silver (Metallic)	YPE – Pewter (Matte)
YRG – Rain Grey (Gloss)	YSTM – Storm Grey (Matte)
YBK – Black (Matte)	YBB – Black (Semi Gloss)
YSKM – Sky (Matte)	YMB – Military Blue (Matte)
YIB – Interstate Blue (Matte)	YSAM – Sapphire (Matte)
YFGM – Forest Green (Matte)	YBR – Bronze (Matte)
YBY – Boysenberry (Matte)	YSRM – Sunset Red (Matte)
YOR – Orange (Matte)	YDAM – Daffodil (Matte)

Choose from one of our Premium Colors with no set-up fee.


For paint chip samples, please email: info@prulite.com




MOUNTING

X1: T-Bar (Flanged)

2'-3' GRID CENTERS REQUIRED (N/A FOR 1'x1' GRID CENTER)




X3R, X7: Hard Ceiling




TRIM DETAILS


X1, X3, X3R: Flanged





X7: Mud Over




ACRYLIC DUST COVER (ADC)




6" TECHZONE



X22: TechZone Interlude




X22: TechZone Slot Grid




ROUGH IN BOX

X7



INCLUDED WITH X1, X3R AND X7

X1, X3R



Rotates to align square dots

Holes for surface mounting as needed

TOP VIEW



Prudential Ltg. reserves the right to change design specifications or materials without notice. Please visit prulite.com for most current data.
© 2014 All rights reserved – All products manufactured at: Prudential Ltg. 1774 E. 21st Street, Los Angeles, CA 90058

Recessed

3

12-12-2023



Stream™ Dot | Recessed 4" Square 'Architectural Accent'




PRUDENTIAL LTG.


PRULITE.COM 213.746.0360

CEILING SYSTEMS


X1: Flanged 1 $\frac{1}{16}$ " T-Bar
2'-3' GRID CENTERS REQUIRED
(N/A FOR 1'x1' GRID CENTER)




X1Z/X27: Armstrong TechZone 6"




X3R: Flanged with Rough-in Box




X3: Flanged without Rough-in Box



X7: Mud-in



X7: Mud-in



Prudential Ltg. reserves the right to change design specifications or materials without notice. Please visit prulite.com for most current data.
© 2014 All rights reserved - All products manufactured at: Prudential Ltg. 1774 E. 21st Street, Los Angeles, CA 90058

Recessed

4

12-12-2023



Stream™ Dot | Recessed 4" Square 'Architectural Accent'




PRUDENTIAL LTG.

PRULITE.COM 213.746.0360

WIRING DIAGRAMS

X1: T-Bar, X3 Flanged Hard Ceiling


Driver in Base Unit with Rough-in Box Included, optional for X3



347V & EML EMERGENCY BATTERY FOR:


X1: T-Bar, X3 Flanged Hard Ceiling

Driver in Rough-in Box, Optional for X3




X7: Hard Ceiling Mud-In

Driver in Rough-in Box




347V & EML EMERGENCY BATTERY FOR:

X7: Hard Ceiling Mud-In




X3: Flanged Hard Ceiling — No Rough-in Box X1Z, X2Z Techzone — Driver in Base Unit



TechZone6

347V & EML EMERGENCY BATTERY FOR:

X3: Flanged Hard Ceiling X1Z, X2Z Techzone



TechZone6

347 WITH EML, CONSULT FACTORY



Prudential Ltg. reserves the right to change design specifications or materials without notice. Please visit prulite.com for most current data.
© 2014 All rights reserved – All products manufactured at: Prudential Ltg. 1774 E. 21st Street, Los Angeles, CA 90058

Recessed

5

12-12-2023



Stream™ Dot | Recessed 4" Square 'Architectural Accent'




PRUDENTIAL LTG.


PRULITE.COM 213.746.0360

REMOTE BOX — MOUNTING DETAIL



X1Z/X2Z: T-BAR (Plenum Access Required)





TechZone6



X7/X3: HARD CEILING — EML/347V (Mount Box Separately)



X7 ROUGH IN BOX — MOUNTING DIMENSIONS



Prudential Ltg. reserves the right to change design specifications or materials without notice. Please visit prulite.com for most current data.
© 2014 All rights reserved – All products manufactured at: Prudential Ltg. 1774 E. 21st Street, Los Angeles, CA 90058

Recessed

6

12-12-2023