



Report No.: 80150237-1
Project No.: 80150237
Client: Prudential Lighting

PHOTOMETRIC TESTING & EVALUATION TO IES LM-79-19

Sample Tested

Pru1-STD-LED35-LO-04-SAL-NU

Prepared for:

Prudential Lighting

1774 East 21st
Los Angeles, CA 90058

Technical Report Number

80150237-1

November 28, 2022

Test Report Prepared and Released by:

K. A. Patel

Keyur Patel
Certifier-I

Test Report Reviewed by:

KC Fletcher

KC Fletcher
Manager

This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government. TM-30-18 is not covered under NVLAP Accreditation. **The results in this report relate only to the sample tested.**

This report shall not be reproduced, except in full, without the approval of CSA Group

Program Description

Photometric and electrical testing of a Pru1-STD-LED35-LO-04-SAL-NU Type C LED Luminaire to IES LM-79-19.

Executive Summary

Sample Tested = Pru1-STD-LED35-LO-04-SAL-NU

Sample Number = 44002765-3

Driver = OSRAM OPTOTRONIC OTi20/120-277/700DIM-1LG2

Luminous Efficacy (Lumens/Watt)	Luminous Flux (Lumens)	Input Power (Watts)	Power Factor	ATHD
88.51	1032.90	11.67	0.9837	8.26%

Spacing Criterion (0-180°)	Spacing Criterion (90-270°)	Stabilization Time (Light & Power)
1.2	1.3	30

* The above results are recorded / derived from measurements made using an Integrating Sphere

This report shall not be reproduced, except in full, without the approval of CSA Group

TABLE OF CONTENTS

Test Sample Pictures.....	4
Test Result.....	5
Photometric Results.....	6
Candela Tabulation.....	9
Photometric Testing Information.....	10
Equipment List.....	11

This report shall not be reproduced, except in full, without the approval of CSA Group

Test Sample Pictures

The following sample was submitted for evaluation:



Prudential Lighting : Pru1-STD-LED35-LO-04-SAL-NU

This report shall not be reproduced, except in full, without the approval of CSA Group

Test Result

The following results were measured after stabilization of the sample in the Integrating Sphere (unless otherwise stated). Stability shall be achieved when the variation (Maximum to minimum) of at least three readings of the light output and electrical power consumption, taken at a maximum of 10 minute intervals over a period of 20 minutes and divided by the last of these measurements chronologically, is less than 0.5%.

Key Photometric Results	Sample Reference
	Pru1-STD-LED35-LO-04-SAL-NU
	Goniophotometer
Luminous Efficacy (Lumens/Watt)	89.00
Total Luminous Flux (Lumens)	1032.9
Stabilization Time (Light and Power)	30 minutes
Total Run Time (Integrating Sphere)	85 minutes
Spacing Criteria (0°-180°)/(90°-270°)	1.2 / 1.28

Electrical Input Results:	Sample Reference
	Pru1-STD-LED35-LO-04-SAL-NU
Input Power (Watts)	11.67
Input Voltage (Volts AC)	120.03
Input Current (Amps)	0.10
Input Frequency (Hertz)	60.0
Power Factor	0.9837
Total Harmonic Distortion (THD A)%	8.26

Additional Information	Sample Reference
	Pru1-STD-LED35-LO-04-SAL-NU
Ambient Temperature	24
Date Tested	11/22/2022

This report shall not be reproduced, except in full, without the approval of CSA Group

Photometric Test Results

Characteristics		Luminance Data (cd/sq.m)			
Total Lumens:	1032.90	Angle In Degrees	Average		
Input Wattage (W):	11.67		0°	45°	90°
Efficacy(lm/W):	88.51	45	7106	6455	6609
Spacing Criterion (0-180°):	1.2	55	6448	5841	6161
Spacing Criterion (90-270°):	1.28	65	5702	5273	5762
Spacing Criterion (Diagonal):	1.36	75	4745	4817	5503
Luminous Length (0-180°):	4.00 ft	85	3381	4754	5580
Luminous Width (90-270°):	0.10 ft				
Luminous Height:	0.03 ft				

Zonal Lumen Summary												
Zone	Lumens	%Fixt		Zone	Lumens	%Fixt		Zone	Lumens		Zone	Lumens
0-20°	117.69	11.4		60-80°	206.64	20.0		0-10°	30.58		90-100°	32.19
0-30°	248.41	24.0		70-80°	86.93	8.4		10-20°	87.11		100-110°	17.12
0-40°	403.83	39.1		80-90°	55.54	5.4		20-30°	130.72		110-120°	7.90
0-60°	710.06	68.7		90-110°	49.32	4.8		30-40°	155.42		120-130°	2.84
0-80°	916.71	88.8		90-120°	57.22	5.5		40-50°	159.95		130-140°	0.60
0-90°	972.25	94.1		90-130°	60.06	5.8		50-60°	146.28		140-150°	0.00
10-90°	941.67	91.2		90-150°	60.65	5.9		60-70°	119.72		150-160°	0.00
20-40°	286.14	27.7		90-180°	60.65	5.9		70-80°	86.93		160-170°	0.00
20-50°	446.09	43.2		110-180°	11.33	1.1		80-90°	55.54		170-180°	0.00
40-70°	425.95	41.2		0-180°	1032.90	100.0		0-90°	972.25		90-180°	60.65

Coefficients of Utilization																		
Effective Floor Cavity Reflectance 0.20																		
RC	80				70				50			30			10			0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
0	118	118	118	118	114	114	114	114	108	108	108	102	102	102	97	97	97	94
1	106	100	95	91	102	97	93	89	92	88	85	87	84	81	82	80	78	75
2	96	87	79	73	92	84	77	72	80	74	69	75	71	67	72	68	64	62
3	87	76	67	60	84	74	66	59	70	63	57	66	61	56	63	58	54	52
4	79	67	58	51	77	65	57	50	62	55	49	59	53	47	56	51	46	44
5	73	60	50	44	70	58	50	43	55	48	42	53	46	41	50	45	40	38
6	67	54	45	38	65	52	44	38	50	42	37	48	41	36	46	40	35	33
7	62	49	40	34	60	48	39	33	46	38	33	44	37	32	42	36	31	29
8	58	44	36	30	56	43	35	30	42	34	29	40	33	29	38	32	28	26
9	54	41	32	27	53	40	32	27	38	31	26	37	30	26	35	30	25	23
10	51	38	30	24	49	37	29	24	35	29	24	34	28	23	33	27	23	21


This report shall not be reproduced, except in full, without the approval of CSA Group

UGR Table												
		Reflectances						Reflectances				
Ceiling Cavity		70	70	50	50	30		70	70	50	50	30
Walls		50	30	50	30	30		50	30	50	30	30
Floor Cavity		20	20	20	20	20		20	20	20	20	20
Room Size		UGR Viewed Crosswise						UGR Viewed Endwise				
X=2H	Y=2H	16.2	17.8	18.7	20.5	21.4	19.0	20.5	19.4	20.9	21.4	
	3H	17.6	19.0	20.0	22.9	23.8	21.5	22.9	21.9	23.3	23.8	
	4H	18.1	19.4	20.4	24.0	25.0	22.7	24.0	23.2	24.5	25.0	
	6H	18.3	19.6	20.6	25.2	26.2	24.0	25.2	24.5	25.7	26.2	
	8H	18.4	19.6	20.6	25.8	26.9	24.6	25.8	25.1	26.3	26.9	
	12H	18.4	19.6	20.6	26.5	27.6	25.4	26.5	25.9	27.0	27.6	
4H	2H	17.2	18.5	19.5	20.7	21.6	19.3	20.7	19.8	21.1	21.6	
	3H	18.9	20.0	21.0	23.2	24.3	22.1	23.2	22.6	0.0	24.3	
	4H	19.4	20.5	21.6	24.5	25.6	23.5	24.5	24.0	25.0	25.6	
	6H	19.8	20.8	21.9	25.9	27.0	25.0	25.9	25.5	26.4	27.0	
	8H	19.9	20.8	21.9	26.6	27.8	25.8	26.6	26.3	27.2	27.8	
	12H	20.0	20.8	21.9	27.4	28.6	26.6	27.4	27.2	28.0	28.6	
8H	4H	20.2	21.1	22.2	24.5	25.7	23.7	24.5	24.2	25.1	25.7	
	6H	20.8	21.6	22.8	26.1	27.3	25.3	26.1	25.9	26.7	27.3	
	8H	21.0	21.7	22.9	26.9	28.1	26.3	26.9	26.9	27.5	28.1	
	12H	21.2	21.7	23.0	27.9	29.2	27.3	27.9	27.9	28.5	29.2	
12H	4H	20.5	21.3	22.4	24.5	25.6	23.7	24.5	24.2	25.0	25.6	
	6H	21.2	21.9	23.1	26.0	27.3	25.4	26.0	26.0	26.6	27.3	
	8H	21.5	22.1	23.3	27.0	28.2	26.4	27.0	27.0	27.6	28.2	


Maximum UGR = 29.2

This report shall not be reproduced, except in full, without the approval of CSA Group

Polar Graph



This report shall not be reproduced, except in full, without the approval of CSA Group



Vertical Angle

Horizontal Angle

Telephone: 949-733-4300
Fax: 949-733-4320
Version 1.2

Photometric Testing Information

The sample was evaluated for photometric and electrical characteristics using a goniophotometer, located in purpose-built, temperature and humidity-controlled, draft free environments

Luminaire Stabilization.

The results were measured after stabilization of the sample in the Goniophotometer (unless otherwise stated). Stability shall be achieved when the variation (Maximum to minimum) of at least three readings of the light output and electrical power consumption, taken at a maximum of 10-minute intervals over a period of 20 minutes and divided by the last of these measurements chronologically, is less than 0.5%.

The goniophotometer Mayer Engineering Type C is calibrated using a frosted tungsten filament FDS/DZE lamp with the following specifications:

The goniophotometer Mayer Engineering Type C is calibrated using a frosted tungsten filament FDS/DZE lamp with the following specifications:

Manufacturer: GE
Part Number: DZE
Bulb Number: 106-A
Voltage: 16.93 Volts DC reference
Calibration Current: 4.863 Amperes
Luminous Intensity: 168.8 Candelas
Calibration Date: 4/25/12 (NIST traceable)

Manufacturer: GE
Part Number: DZE
Bulb Number: 106-B
Voltage: 16.45 Volts DC reference
Calibration Current: 4.79 Amperes
Luminous Intensity: 145.3 Candelas
Calibration Date: 4/25/12(NIST traceable)

Manufacturer: GE
Part Number: DZE
Bulb Number: 106-C
Voltage: 16.57 Volts DC reference
Calibration Current: 4.829 Amperes
Luminous Intensity: 157.0 Candelas
Calibration Date: 4/25/12 (NIST traceable)

A Yokogawa WT310 Power Analyzer was used to measure all electrical characteristics of the sample.

This report shall not be reproduced, except in full, without the approval of CSA Group

Equipment List: Goniophotometer Type C (Mirror 2)

Description	Manufacturer and Model Number	CSA Instrument Reference Number	Calibration Due Date
Optometer	Gigahertz Optik P9801	OPT400	N/A
Programmable DC Power Supply	Chroma Instruments 62012P-80-60	DCP300	N/A
Regulated Power Supply	Chroma Instruments 61602	AC301	N/A
Power Analyzer	Yokogawa WT310-E	POA400	6/27/2023

* All equipment is calibrated to ISO / IEC 17025-2017 guidelines.

Accreditation

- This report, and use of the NVLAP logo, shall not be used by a client to claim certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S. Government.
- This report, and use of the CSA logo, shall not be used by a client to claim certification, approval, or endorsement by CSA.
- This test report, may contain sections with product performance criteria, which has been specified by certification program(s) not affiliated with NVLAP. TM-30-18 is not covered under NVLAP Accreditation.
- This test report, contains sections with test data recorded within the scope of this labs accreditation through NVLAP. In these instances, the NVLAP Logo and associated testing lab code will be present on the header of the first page and last page.



This report shall not be reproduced, except in full, without the approval of CSA Group