Prudential Lighting

Light measurement results

Print date 8/10/2026

Laboratory and Equipment

Test lab	Viso LabSpion - serial: 2435469709 sensor serial: 0895736217 - T
Spectrometer Manufacturer and Model	LabSpion – Type C, horizontal
Measurement date	8/4/2026

Measurement Conditions

Tested c-planes	72 planes – 5.00°
Tested gamma resolution	1.00°
Input Power	23.25 W

Tested Light Source


Luminaire	WETBPRO4-LIN-FLSH-LED35-MO-04-SAL-NU-SC-DM01
Basic Luminous Shape	NONE
Item No.	
Manufacturer	Prudential Lighting
Description	

Main Light Measurement Results

Output – Total Lumen (Up% / Down%)	2992 lm – 2.54% / 97.46%
Efficiency	128.7 lm/W
Peak Intensity	1057 cd
Correlated Color Temperature, CCT	3473 K
Color Rendering Index	CRI 84.8

Polar light distribution diagram

Unit: 0-100% of peak intensity



109.3°


C0 - C180
C90 - C270

η = 100%

Zonal Lumen Summary:

VA/HA	0°	22.5°	45°	67.5°	90°
0°	1056 cd	1056 cd	1056 cd	1056 cd	1056 cd
5°	1051 cd	1050 cd	1052 cd	1050 cd	1049 cd
15°	1006 cd	1008 cd	1008 cd	1006 cd	1005 cd
25°	926.2 cd	926.1 cd	923.8 cd	923.1 cd	924.6 cd
35°	815 cd	813.2 cd	809.2 cd	809.3 cd	811 cd
45°	680.5 cd	676.7 cd	670.8 cd	671.8 cd	675.3 cd
55°	527.8 cd	525.7 cd	518.5 cd	520.9 cd	523.5 cd
65°	361.6 cd	360.9 cd	355.7 cd	358.5 cd	360.9 cd
75°	189.8 cd	192.3 cd	191.9 cd	195.8 cd	195.6 cd
85°	38.46 cd	47.22 cd	50.85 cd	50.08 cd	46.84 cd
90°	6.811 cd	6.248 cd	7.488 cd	5.766 cd	2.86 cd

Spectral power distribution




Prudential Lighting

Light measurement results

Print date 8/10/2026

Luminous Intensity diagram

Unit: 0-100% of peak intensity



Main Values

Output (total Lumen)	2992 lm
Lumen Up% / Down%	2.54% / 97.46%
Peak Intensity	1057 cd
Beam Angle (50%-FWHM)	109.3°

EU Ecodesign parameters


Directionality (DLS or NDLS)	NDLS
Ecodesign Useful Luminous Flux	2992 lm
Ecodesign Energy Class	E

Intensity Ratio

In 120° cone	77.07%
In 90° cone	52.86%

Linear distribution diagram

Intensity [cd]




Prudential Lighting

Light measurement results

Print date 8/10/2026


Iso-intensity Diagram (Iso-candela)



90 %	951.5 cd
80 %	845.8 cd
70 %	740.1 cd
60 %	634.4 cd
50 %	528.6 cd
40 %	422.9 cd
30 %	317.2 cd
20 %	211.5 cd
10 %	105.7 cd

Peak intensity: 1057.3 cd
Number of c-planes: 72

Iso-illuminance Diagram (Iso-lux)



50.0 %	58.7 lx
30.0 %	35.2 lx
10.0 %	11.7 lx
5.0 %	5.87 lx
3.0 %	3.52 lx

Peak illuminance: 117 lx
Mounting height: 3 m
Number of c-planes: 72

Prudential Lighting


Light measurement results

Print date 8/10/2026


Color details

Correlated Color Temperature, Target	CCT = 3473 K	MacAdam Steps	SDCM = NaN
Correlated Color Temperature, Measured	CCT = 3473 K	Color deviation from BBL	Duv = 0.0006
Color Rendering Index	CRI 84.8	Color coordinates CIE 1931	(x;y) = (0.4077;0.3932)
Color Rendering Index, R9 (red)	R9 = 14.0	Color coordinate CIEs 1960	(u;v) = (0.2362;0.3418)
Color Rendering TM30-18	Rf 85.8	Color coordinate CIEs 1976	(u';v') = (0.2362;0.5126)
	Rg 96.0	Color Quality Scale	CQS = 84.5


CIE 1931 Chromaticity diagram




Spectral power distribution



CIE 1931 Chromaticity - zoomed




Color Rendering Index per reference color (CIE 1995)




CRI R values, only R1-R8 are used to calculate final CRI value

R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15
83.5	91.2	96.8	84.2	83.5	88.7	85.7	64.6	14.0	79.5	84.5	67.1	85.6	98.6	75.9

CIE 1931 Chromaticity - SDCM



TM30-18 Rf-values per hue bin



TM30-18 Rf-values per hue bin

C1	C2	C3	C4	C5	C6	C7	C8	C9	C10	C11	C12	C13	C14	C15	C16
81.4	83.7	81.0	90.0	92.0	94.4	91.2	93.4	89.1	81.8	80.8	85.0	89.7	81.7	80.8	79.1


Prudential Lighting

Light measurement results

Print date 8/10/2026

Color details - ANSI/IES TM-30-18 Color Rendition Report


Color Vector Graphic




Color Distortion Graphic



Gamut Index vs. Fidelity Index




Color Rendition by Color Evaluation Sample (CES)




Color evaluation sample CES01 through CES99

Local Color Fidelity (per hue bin)



Local Chroma Shift (per hue bin)



CIE x	0.4077
CIE y	0.4077
CIE u'	0.2362
CIE v'	0.5126


CIE	13.3-1995
Ra	84.8
R9	14.0

Prudential Lighting

Light measurement results


Print date 8/10/2026

Beam details



Luminaire budgetary diagram

LAMPS (number of lamps)



Intensity details

Beam intensities from 1 – 20 m

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	m
3.3	6.6	9.8	13.1	16.4	19.7	23	26.2	29.5	32.8	36.1	39.4	42.7	45.9	49.2	52.5	55.8	59.1	62.3	65.6	ft
1056	264	117	66	42	29	22	16	13	11	9	7	6	5	5	4	4	3	3	3	lux
98.1	24.5	10.9	6.1	3.9	2.7	2	1.5	1.2	1	0.8	0.7	0.6	0.5	0.4	0.4	0.3	0.3	0.3	0.2	fc

Intensities in 0° c-plane

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°	γ
1056	1051	1034	1006	971	926	875	815	750	681	606	528	445	362	276	190	108	38	7	6	cd
100%	100%	98%	95%	92%	88%	83%	77%	71%	64%	57%	50%	42%	34%	26%	18%	10%	4%	1%	1%	of 0°val

Intensities in 90° c-plane

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°	γ
1056	1049	1032	1005	969	925	871	811	746	675	601	523	443	361	278	196	117	47	3	2	cd
100%	99%	98%	95%	92%	88%	83%	77%	71%	64%	57%	50%	42%	34%	26%	19%	11%	4%	0%	0%	of 0°val

Intensities in 180° c-plane

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°	γ
1056	1051	1036	1009	976	931	880	820	754	682	606	528	444	359	271	185	105	36	3	4	cd
100%	100%	98%	96%	92%	88%	83%	78%	71%	65%	57%	50%	42%	34%	26%	18%	10%	3%	0%	0%	of 0°val

Intensities in 270° c-plane

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°	γ
1056	1050	1033	1006	969	924	871	812	747	677	602	524	444	362	280	197	117	48	6	6	cd
100%	99%	98%	95%	92%	88%	83%	77%	71%	64%	57%	50%	42%	34%	26%	19%	11%	5%	1%	1%	of 0°val

Prudential Lighting

Light measurement results

Print date 8/10/2026

UGR Table

Corrected, comprehensive UGR table according to 117-1995, S/H ratio=0.25

Reflectances											
ρ Ceiling	70	70	50	50	30	70	70	50	50	30
ρ Walls	50	30	50	30	30	50	30	50	30	30
ρ Floor	20	20	20	20	20	20	20	20	20	20
Room size	**Viewed Crosswise**					**Viewed Endwise**				
H = mouting height above eye level	(Viewing direction orthogonal to lamp length axis)					(Viewing direction parallel to lamp length axis)				
X **Y**										
n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
Variations with the observer position for the luminaire spacings, S:										
n/a	n/a					n/a				
n/a	n/a					n/a				
n/a	n/a					n/a				

UGR data could not be calculated due to missing light source dimensions. Go to Edit -> Photometric -> Dimensions and set the source dimensions.

Coefficients of utilization

Ceiling reflectance	80				70				50			30			10			0
Wall reflectance	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
Floor reflectance	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20
RCR	(Room Cavity Ratio)				Room values are expressed as percentage of Lumen delivered to the task surface													
0	118.4	118.4	118.4	118.4	115.4	115.4	115.4	115.4	109.7	109.7	109.7	104.5	104.5	104.5	99.7	99.7	99.7	97.5
1	108.2	103.4	99.2	95.3	105.2	100.9	97.0	93.5	96.2	93.0	90.1	91.9	89.3	86.9	87.9	85.8	83.9	81.6
2	98.4	90.1	83.3	77.6	95.5	88.0	81.8	76.5	84.1	78.8	74.3	80.4	76.1	72.2	77.0	73.5	70.3	68.0
3	89.7	79.2	71.0	64.5	87.0	77.4	69.8	63.8	74.0	67.6	62.3	70.9	65.5	60.9	68.1	63.5	59.6	57.3
4	82.1	70.1	61.4	54.7	79.6	68.6	60.5	54.1	65.8	58.7	53.1	63.2	57.1	52.1	60.7	55.5	51.2	48.9
5	75.5	62.7	53.7	47.1	73.2	61.4	53.0	46.7	59.0	51.6	45.9	56.7	50.3	45.2	54.6	49.0	44.5	42.3
6	69.7	56.4	47.5	41.1	67.6	55.3	46.9	40.8	53.3	45.8	40.2	51.3	44.7	39.7	49.5	43.7	39.1	37.0
7	64.6	51.2	42.4	36.3	62.8	50.2	41.9	36.1	48.4	41.0	35.6	46.8	40.1	35.2	45.2	39.3	34.8	32.7
8	60.2	46.7	38.2	32.4	58.5	45.9	37.8	32.2	44.3	37.0	31.8	42.9	36.3	31.5	41.5	35.6	31.1	29.2
9	56.2	42.8	34.6	29.1	54.7	42.1	34.3	29.0	40.8	33.7	28.7	39.6	33.1	28.4	38.4	32.5	28.1	26.3
10	52.7	39.5	31.6	26.4	51.3	38.9	31.4	26.3	37.8	30.8	26.0	36.7	30.3	25.8	35.6	29.8	25.6	23.8

Prudential Lighting


Light measurement results

Print date 8/10/2026

Power details

Input power	
Frequency of input power	60.0 Hz
Power feed to light source	23.25 W
RMS Input voltage feed V,RMS	120 V
RMS Input current feed I,RMS	0.20 A
Volt-Amp or apparent power = V,RMS*I,RMS	23.6 VA
Displacement factor of AC power feed	0.99
Power factor of AC current feed	0.99
Total harmonic distortion of the current	8.381%
Total harmonic distortion of the voltage	0.0954%

Input power curve




Efficiency

Radiated power efficiency	38.82
Lumen efficiency	128.7 lm/W

Stabilization details

Warmup Conditions		Color Temperature Change	
Stable period	n/a	CCT start	NaN K
Stable change max	n/a%	CCT shift	NaN K
Minimum time	n/a	CCT end	3473 K
Warmup Result		**Output Change**	
Total warmup time	n/a	Output start	NaN lm
Warmup variation	NaN%	Output change	NaN lm
		Output end	2992 lm

Stabilization Curve



Prudential Lighting

Light measurement results

Print date 8/10/2026

Flicker TLA details

Flicker Meter Type	Viso Systems LabFlicker
Frequency of input power	60.0 Hz
Flicker/TLA sample rate	NaN samples/s

Measurement time

PstLM	180 sec.
All other indices	1,5 sec,

Flicker indices according to Illuminating Engineering Society (IES)

Flicker frequency	NaN Hz
Percent Flicker	NaN %
Flicker index	NaN

TLA indices (re IEC TR 61547-1, IEC 61000-3-3 and IEC 61000-4-15)

PstLM value (F < 80 Hz)	NaN
SVM value (80 < F < 2000 Hz)	NaN


Flicker indices according to California Energy Commission (CEC) 2016b

JA8/10 40 Hz	NaN %
JA8/10 90 Hz	NaN %
JA8/10 200 Hz	NaN %
JA8/10 400 Hz	NaN %
JA8/10 1000 Hz	NaN %


Flicker indices according to Lighting Research Center (2015)

Perception metric, Assist Mp	NaN

Flicker frame (frame of one flicker period in time domain)



Flicker FFT (flicker curve in frequency domain)



IEEE 1789 Frequency/modulation plot

